

“Paving the way to excellence with colour and texture”

FOR A FREE ESTIMATE CALL YOUR LOCAL CONTRACTORS

**CREATIVE IMPRESSIONS**

Creative Impressions Ltd. Unit 237, Walton Summit Park,  
Bamber Bridge, Preston, Lancs., PR5 8AG, England.  
Registered in England No. 2496456  
Tel. 01772 335435 Fax. 01772 335434  
e-mail: sales@creative-impressions.com  
www.creative-impressions.com




Superseal™

The only solution for sealing decorative concrete

- Seals, protects and enhances the surface of all decorative textured concrete and block paving.
- A tough, non yellowing, acrylic resin coating that protects the surface from oil and most chemical spillage.
- Prevents algae build up and inhibits moss growth.
- Easily applied by sprayer, brush or roller and dries quickly to a hard durable sheen.

The **Art** of Decorative Concrete

**CREATIVE IMPRESSIONS**





# Superseal™

- Easily applied by sprayer, brush or roller and dries quickly to a hard durable sheen.
- Solvent based Acrylic solution produces a hard, durable clear film. It is non-yellowing and has excellent resistance to water, alkalis and acids.
- Deeply penetrates high compaction blocks and concrete slabs, offering lasting protection against attack from oil and chemical spills.

“Paving the way to excellence with colour and texture”



Before



After



Before



After

**AVAILABILITY** SUPERSEAL™ is available in 5ltr and 25ltr UN approved drums.  
**FINISHES** SUPERSEAL™ is available in primer, gloss and matt finishes.  
**COVERAGE** SUPERSEAL™ covers 3-6m<sup>2</sup> per/ltr if spray applied, slightly less if applied by brush or roller.

## INSTRUCTIONS FOR USE

**SURFACE PREPARATION** The surface to be sealed must be washed carefully to remove all traces of powder release. Creative Impressions “Pre-Seal Wash” should be used as this ensures all residual release powder is removed. If this process is not carried out correctly, the sealer may not penetrate the concrete surface and could result in small areas “plucking” off the surface. Before applying the sealer ensure the surface is dry, especially in the joints and deep texture. A power leaf blower can assist in removing this water.

**APPLICATION** We recommend that **SUPERSEAL™** Acrylic sealer is applied in a two-coat application. The first coat should be one of our Superseal Primer range. After the first coat has dried sufficiently (2-3hrs @ 10°C) the final, full strength coating should be applied.

**MAXI-GRIP** If a non-slip surface is specified, our “MAXI GRIP” anti-slip additive should be added to the sealer. Care should be taken to thoroughly mix the additive into the sealer at a rate of 1 tub per 25ltr. For maximum protection, add to top coat only.

**SUPERSEAL™ PLUS** Manufactured specially for Garage and Service Station forecourt use, where maximum resistance to petrol and diesel spillage is required – be sure to specify new **SUPERSEAL™ PLUS**. New formulation **SUPERSEAL™ PLUS** dries to a “diamond hard” film that is impervious to attack from petroleum products.

## ADDITIONAL SEALERS AVAILABLE:

**HYDROSEAL™** is available in 5ltr and 25ltr UN approved drums.  
**HYDROSEAL™** Primer and top coat sealer specially formulated for use in damp conditions also available in the plus range.

**GEMSEAL™** Water based sealer is also available in 5ltr and 25ltr drums.



Matt Finish

Gloss Finish