



COPPEROL

Product description:

Copperol is an alkyd based oil that is very deep penetrating. The product is intended for wood outdoors, wood that is exposed for humidity, such as sleepers, gate posts, bridges, etc. The product provides protection against moisture and prevents the growth of algae and mould. Copperol contains linseed oil, which together with low viscosity, gives a deep penetration. Brown Copperol is not possible to overcoat with paint. Copperol is produced in Sweden and is a proven product used as wood coating agent through decades.

TECHNICAL DATA:

Area of application	Outdoors
Binder	Boiled linseed oil /alkyd
Volume Solids	19%
Density	0,85 g/cm ³
Thinner/Cleaning	White spirit/naphtha
Material consumption	4–12 m ² /L
Temperature at painting	Minimum +5°C
Tools for painting	Brush, sponge or cloth
Dust dry	1–2 h
Re-paintable	5–6 h, NB! Only re-paintable when not tinted
Shelf life	2 years if unopened, frost free storage
Colour	Clear
Flammability	2b
VOC category	(Cat. A/h): 750 g/l (2010)



COPPEROL

How to use

Pre-painting

Always start by reading the instructions on the label. It is important to be thorough from the beginning. The use of correct tools and a carefully performed base is the foundation for a successful result. Stir well from the bottom before starting to paint.

The air and surface temperature is also important for the end result. Do not paint if it is below +5°C. The surface must be clean, dry and firm. Brush or scrape off loose old paint and/or porous and degraded wood.

Painting

Apply the product fluently into the surface. Pay special attention to treat end grain and timber joints well. To achieve maximum penetration: place the wood into a container with Copperol and let soak for a couple of hours.

Post-painting

Wipe off the tools thoroughly before cleaning with white spirit. Seal the tin carefully after use and keep out of reach for children. Liquid residues may not be poured down the drain, but be submitted to the local collection point. Protect the environment, like we do.

N.B.! Cloths soaked in Copperol may spontaneously combust and must therefore be neutralised.

Maintenance

We recommended to repeat the treatment several times pro year, especially in the autumn.