

Product Description:

Deka Silan is a solvent-based high-performance sealer formulated for porous external natural stone surfaces, such as slate, terracotta, yorkstone, quarry tile, limestone, concrete and other types. It provides high-quality protection that prevents water-based stains and general grime & dirt from penetrating into the surface, making it easier to clean and maintain.

Technical Data:

Color: clear

Theoretical Coverage: 4-10m²/L

** depends on substrate, way of application, temperature etc.*

Density: 0.82 g/cm³

Shelf life: 12 months (20-25°C). Product should be stored in ventilated area; no direct sunlight; no low temperature.

Application and instructions:

- Surface must be clean, totally dry, remove any loose debris.
 - Ensure you have adequate safety wear, i.e. gloves, suitable protective eyewear, face mask & clothing.
 - Leave the surface for a minimum of 72 hours with clear and dry weather to ensure the surface is completely dry and ready to be sealed. Make sure also that weather conditions are favourable before commencing.
- Application temperature range: 15° to 23°C.
- DO NOT DILUTE
 - Sealer should be applied thinly and evenly with brush, paint roller or spraying device.
 - Allow 45-60 minutes drying time before applying the second coat, repeating the same process.
 - Always try the product in an inconspicuous area prior to use.
 - Surfaces that are not to be sealed should be protected with masking material.
 - Sealer COULD NOT be used on polished, grinded, glazed or damp surfaces.

Packaging:

1L; 5L

Warranty & Safety Precautions:

The information herein is believed to be reliable, but unknown risks may be present. Epolac warrants only that the materials shall be of merchantable quality. This warranty is in lieu of all other written or unwritten, expressed or implied warranties. Epolac expressly disclaims any warranty of fitness for a particular purpose, or freedom from patent infringement. Accordingly, Buyer assumes all risks whatsoever as to the use of these materials. Buyer's exclusive remedy as to any breach of warranty or negligence claim shall be limited to the purchase price of the materials. Failure to strictly adhere to recommended procedures shall relieve Epolac of all liability with respect to the materials or the use thereof.

Refer to the SDS sheets before use. FOR PROFESSIONAL USE ONLY.

Technical data sheet and instructions are subject to change without notice.

Contact your Epolac representative for additional information.